

Technical drawing of a mechanical part, showing a top view and a side view. The top view is a circular component with a central hole and four rectangular slots. The side view shows the component's profile with a central vertical hole and a horizontal slot. Dimensions are provided in millimeters (mm).

Top View Dimensions:

- Overall width: 31
- Overall height: 2.3 ± 0.1
- Central hole diameter: ϕ
- Slot width: 60°
- Slot depth: 9.5

Side View Dimensions:

- Overall height: 0.8
- Top flange thickness: 1.3
- Central hole diameter: $\phi 6^{+0}_{-0.1}$
- Internal hole diameter: $\phi 6$
- Internal hole depth: ∞

Labels:

- 黄黑 (Yellow/Black)
- 棕白红 (Brown/White/Red)

Technical drawing of a cable gland assembly. The drawing shows a cross-section of the assembly with the following dimensions and labels:

- Top dimension: $\varnothing 1.5_{-0.01}^0$
- Left vertical dimensions: 31.5REF, 18.5, 11
- Inner diameter: $\varnothing 20$
- Right horizontal dimension: 3.6
- Bottom vertical dimension: 104 ± 15
- Label: UL1061 26#
- Symbol: @

相数	PHASE	4	COMMENT
步矩角	STEP ANGLE	18 ° /STEP	
电压	VOLTAGE	4.5 V	
驱动方式	EXCITATION	4-3 UNIPOLAR	
相电流	CURRENT	0.12 A/PHASE	
电阻	RESISTANCE (20℃)	38±7% ohm/phase	
定位转矩	DETENT TORQUE	10 g.cm Max	
保持转矩	HOLDING TORQUE	25g.cm min	
起动转矩	PULL-IN TORQUE	10g.cm (150pps)	
最大自起动频率	MAX PULL-IN RATE	400PPS (4.5V 4-3驱动 1#仪器)	
转动惯量	ROTOR INERTIA	0.4g.cm.cm	
噪音	NOISE	<55db	
温升	TEMPERATURE RISE	<25	
绝缘等级	INSULATION CLASS	E	
绝缘电阻	INSULATION RESISTANCE	>100MΩ (DC 500V)	
绝缘耐压	DIELECTRIC STRENGTH	AC 500V RMS 1min	
使用温度	OPERATING TEMPERATURE	-10℃-55℃	
重量	WEIGHT	23g	

底图总号		@	2			DGF	190423				常州宝来电器有限公司 Baolai Electric Appliance		
		标记	处数	分区	更改文件号	签名	年. 月. 日						
		设计	DGF	190423	标准化			阶段标记		重量	比例	info@baolai-cn.com www.baolai-cn.com	
日期	签名	审核									2:1		
		工艺			批准			共 1 张 第 1 张					

幅面: 4[#]